



**Acrylic Roof Primer (Solvent-Based)**  
(Product # 81050)

**DESCRIPTION:** Acrylic Roof Primer is a clear, fast drying, solvent based primer that provides excellent adhesion to most surfaces. It will provide an excellent base to insure adhesion over oily, weathered asphalt, built-up and metal roofs. Acrylic Roof Primer provides a unique combination of hardness and flexibility without tracking at elevated temperatures. The resultant film will accommodate roof flexing while tying up loose dust.

**USES:** Acrylic Roof Primer should be used as a primer prior to applying Storm Seal Elastomeric Roof Coating. When applied over metal, weathered asphalt, dusty or oily substrates, it dries quickly to provide a tack free base coat.

**Caution:** This product is not intended for use over coal tar, new asphalt roofs which have weathered less than 90 days, vinyl or rubber substrates.

**PREPARATION:** Surfaces to be coated should be power washed or swept to remove as much dirt, dust, rust and grease or oil as possible. Allow surfaces to dry prior to application.

**NOTE:** The use of Acrylic Roof Primer is not a substitute for proper cleaning of roof surfaces prior to top-coating.

**APPLICATION:** Acrylic Roof Primer may be brushed rolled or sprayed. Its low viscosity allows the use of a typical garden sprayer to ease application. Apply in a thin uniform film at a rate of ½ - ¾ gallon per 100 square feet. The dried film should be top-coated within 21 days of application. If top-coating is delayed over 21 days or in extremely dusty conditions, it is recommended that the primer be re-applied prior to top-coating.

**COVERAGE RATE:** ½ to ¾ gallon per 100 square feet.

**PACKAGING:** 55-gallon drum, 5-gallon pail

**CLEAN UP:** Tools may be cleaned with Xylene or Mineral Spirits. Use caution when handling any hazardous material.

**CAUTION:** Use only with adequate ventilation. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF THE REACH OF CHILDREN.** Keep container covered when not in use. See MSDS for further information.