



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 20-May-2015

Revision Date 20-May-2015

Version 1

Product identifier

Product Name Asphalt Adhesive

Other means of identification

Product Code 81200

Synonyms Blind Nail Cement - Cold Method Lap Seal

Recommended use of the chemical and restrictions on use

Recommended Use Cold process Adhesive for bonding roofing sheets.

Uses advised against For exterior use only. Do not use indoors. Not recommended for hot mop felts such as 15# or 30# felt.

Details of the supplier of the safety data sheet

Manufacturer Address FBC Chemical Corp.
P.O. Box 599
634 Route 228
Mars, Pennsylvania 16046
(724) 625-3116

Emergency telephone number

Company Phone Number 724 625 3116

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300
Outside USA and Canada: 1-703-527-3887

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

Suspected of causing cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways

Flammable liquid and vapor

**Appearance** Viscous**Physical state** Liquid**Odor** Solvent (Mineral Spirits)**Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces.
Keep container tightly closed when product is not in use.
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

• May be harmful in contact with skin
Unknown acute toxicity No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance****Mixture**

This product is a mixture.
This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name**Synonyms****Chemical nature**

No information available.

Chemical Name	CAS No.	Weight-%	Trade Secret
Asphalt (at Ambient Temperature)	8052-42-4	60 - 70%	*
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	20 - 30%	*
Kaolin	1332-58-7	0 - 10%	*
Hydrated Aluminum-Magnesium Silicate (Attapulgate)	12174-11-7	0 - 10%	*
Cellulose Fiber	9004-34-6	0 - 10%	*
Nonane	111-84-2	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin contact	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause skin irritation. May cause eye irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

No information available.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

Other Information Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.

Incompatible materials Strong acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA. .

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt (at Ambient Temperature) 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

		(vacated) TWA: 525 mg/m ³	
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Hydrated Aluminum-Magnesium Silicate (Attapulgate) 12174-11-7	TWA: 1 mg/m ³ respirable fraction	-	-
Cellulose Fiber 9004-34-6	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ (vacated) STEL: 10 mg/m ³	TWA: 1 mg/m ³
Nonane 111-84-2	TWA: 200 ppm	(vacated) TWA: 200 ppm (vacated) TWA: 1050 mg/m ³	TWA: 200 ppm TWA: 1050 mg/m ³

Appropriate engineering controls**Engineering Controls**

Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of solvent vapors. Ventilation must be sufficient to maintain solvent vapor concentrations below the TWA limits outlined above.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing that is resistant to chemical penetration.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

General Hygiene Considerations

Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Odor	Solvent (Mineral Spirits)
Appearance	Viscous	Odor threshold	No information available
Color	Black		
Property	Values	Remarks • Method	
pH	Not applicable	Not applicable	
Melting point/freezing point	No information available		
Boiling point / boiling range	> No information available		
Flash point	> 40.5 °C / > 105 °F	Setaflash	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limit in Air		No data available.	
Upper flammability limit:	No information available		
Lower flammability limit:	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	1.00 - 1.05	Water = 1g/ml	
Water solubility	Insoluble		
Solubility in other solvents	Soluble in aromatic and aliphatic solvents.		
Partition coefficient	No information available	No data available.	
Autoignition temperature	No information available		

Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	Vapor accumulation could flash or explode if ignited.
Oxidizing properties	None

Other Information

Softening point	Not applicable
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Not applicable	Not applicable
----------------	----------------

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to avoid

Avoid static discharge. Avoid heat, sparks, and open flame.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.
Inhalation	Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin contact	May cause irritation.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Component Information

* The IARC Monograph (Vol. 103, 2013, Bitumen and Bitumen Emissions) defines Asphalt as 'Group 2B, Possible Carcinogen to Humans'. This definition is based on studies of exposure to Asphalt fumes at elevated temperatures. The Monograph states that temperature plays an important role in determining the degree of exposure and also the carcinogenic potential of bitumen emissions. This same Monograph states that Asphalt is non volatile at ambient temperature. There is no data presented in the Monograph to demonstrate that Asphalt at ambient temperature is considered a carcinogen. Since the normal use of this product is at ambient temperature, the Asphalt used in this product is not listed as a carcinogen. No other national or international agency has defined Asphalt as a carcinogen.

** No significant exposure to Crystalline Silica (Quartz) is thought to occur during the use of

products in which Crystalline Silica (Quartz) is bound to other materials, such as in paints and coatings. As one reference, see California Office of Health Hazard Assessment at: http://www.oehha.org/prop65/CRNR_notices/safe_use/sylicasud2.html

*** The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states: "Operators in user industries who handle fluffy or pelleted Carbon Black during rubber, paint and ink production are expected to have significantly lower exposures to Carbon Black than workers in Carbon Black production. Other workers in user industries who handle it occasionally have little opportunity for exposure. And further... "End-users of these products (rubber, ink or paint) are unlikely to be exposed to airborne Carbon Black particles, which are bound within the product matrix."

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Cellulose Fiber 9004-34-6	> 5 g/kg (Rat)	> 2 g/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h
Nonane 111-84-2	-	-	= 3200 ppm (Rat) 4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Can cause skin irritation.
Serious eye damage/eye irritation Irritating to eyes.
Irritation Irritating to eyes, respiratory system and skin.
Corrosivity Not classified.
Sensitization May cause sensitization of susceptible persons.
Germ cell mutagenicity This product does not contain any ingredients that cause germ cell mutagenicity.
Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Hydrated Aluminum-Magnesium Silicate (Attapulgite) 12174-11-7	-	Group 2B Group 3	-	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
 A2 - Suspected Human Carcinogen
 A3 - Animal Carcinogen
 A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
 Group 2A - Probably Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not classifiable as a human carcinogen.

NTP (National Toxicology Program)

Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity None known.
Developmental Toxicity None known.
Teratogenicity None known.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard No information available.

Numerical measures of toxicity - No information available

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 6,753.00
ATEmix (dermal) 2,701.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

100% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Asphalt (at Ambient Temperature) 8052-42-4	6

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN 1993
Proper shipping name Flammable liquid, n.o.s.(Petroleum distillates)
Hazard Class 3
Packing Group III
Special Provisions Not Regulated in Containers <119 Gallons(450 Liters)
Emergency Response Guide Number 128

TDG unknown

MEX unknown

ICAO (air) unknown

IATA unknown

IMDG unknown

RID unknown

ADR unknown

ADN unknown Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

DSL/NDL All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Hydrated Aluminum-Magnesium Silicate (Attapulgite) - 12174-11-7	Carcinogen

U.S. State Right-to-Know Regulations

This product contains the following substances regulated by various State Right-to-Know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt (at Ambient Temperature) 8052-42-4	X	X	X
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	X	X	X
Kaolin 1332-58-7	X	X	X
Cellulose Fiber 9004-34-6	X	X	X
Nonane	X	X	X

111-84-2

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection -
<i>Chronic Hazard Star Legend</i>	* = Chronic Health Hazard			

Prepared By FBC Administrative Services Department

Issue Date 20-May-2015

Revision Date 20-May-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet