



## **Driveway Crack Sealant – Product #81850** **(Trowel Grade Asphalt Sealant)**

**DESCRIPTION:** Driveway Crack Sealant is a heavy-bodied sealant formulated to remain strong and flexible in any type of weather. Driveway Crack Sealant is fortified with fibers to add reinforcement. It blends with the blacktop surface to prevent water seepage and the damage it can cause. . This dramatically increases the life of the asphalt surface. Once cured, Driveway Crack Sealant may be topcoated with either Coal Tar or Asphalt based driveway sealers.

**USES:** Fills cracks and prevents water penetration in cracks up to 1” wide.

**PREPARATION:** Remove all dust, dirt, debris and loose particles with a stiff brush or broom. If air pressure is available, blow cracks clean and dry. Apply without heating at temperatures above 50 degrees Fahrenheit. In cold weather, store at room temperature for 24 hours prior to use to ease application.

**APPLICATION:** Do not thin. Use Crackfiller directly as supplied. Press Crackfiller directly into cracks using a putty knife or squeegee. Use firm pressure to insure all voids are sealed. The finished surface may be smooth using a putty knife dipped in Mineral Spirits. Driveway Crack Sealant will dry to a resilient black sealant in 24-48 hours.

**TIPS:** 1. For best results, cracks deeper than ½” should be sealed in two layers allowing 24 hours between applications.  
2. If immediate use is required, fill crack to ¼” from top surface and lightly cover Driveway Crack Sealant with sand. This will prevent tracking.

**CLEAN UP:** Tools may be clean with Mineral Spirits. Use caution when using any Combustible solvent.

**CAUTION:** Contains petroleum distillate. Do not take internally. If swallowed, call physician immediately. Do not induce vomiting unless directed by a physician to do so. Avoid prolonged or repeated breathing or contact with skin. **KEEP OUT OF REACH OF CHILDREN!**

**PACKAGING:** 5 gallon, 1 gallon & 10.5 ounce Caulking cartridge