Distributed By: Aluminum Coatings Manufacturers, INC. 7301 Bessemer Ave

Cleveland, OH 44127 Tel: (216) 341-2000

MATERIAL SAFETY DATA SHEET

Issue Date: December 30, 1988

PRODUCT

Greige and printed fabrics.

Polyester (polyethylene terephthalate polymer) stitchbonded and knit fabrics. Some fabrics finished with acrylic resins and hand modifiers.

HAZARDOUS INGREDIENTS

There are no hazardous ingredients as defined in the *Code of Federal Regulations, Title 29, Part 1910.1200.

PHYSICAL HAZARDS

Polyester fabrics will melt at approximately 500*F. and will burn if exposed to flame. Decomposition products generated from molten polymer may be subject to auto ignition. Combustion products will be comprised of carbon, hydrogen, oxygen, and nitrogen. The exact composition will depend on the conditions of combustion.

HEALTH HAZARD INFORMATION

Exposure to Tietex fabrics would pose no significant health problems under normal conditions of handling and use.

EXPOSURE CONTROL METHODS

General ventilation is suggested. Recirculating systems should, whenever practical, be operated in the bypass mode to avoid concentrating air contaminants in the work space.

Fire fighters should protect themselves from decomposition and combustion products that may include carbon monoxide and other toxic gases.

SAFE HANDLING PROCEDURES

Customary personal hygiene measures such as washing hands after working with such fabrics is recommended.

To the best of our knowledge, the information contained herein is accurate. However, Tietex Corporation does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*Federal Register—Page 53342, Paragraph 5:ii; Page 53343, Vol. 48, No. 228, 1983