



•634 Route 228 • P.O. Box 599 • Mars, PA. 16046 • 724-625-3116 • FAX 724-625-1640
 •4111 Walden Ave • Lancaster, NY 14086 • 716-681-1581 • FAX 716-681-1513
 •900 W. Smith Rd. • Medina, OH 44256 • 330-723-7780 • FAX 330-723-7780
 •7301 Bessemer Avenue • Cleveland OH 44127 • 216-341-2000 • FAX 216-341-5833



STITCHBOND POLYESTER MAT

Stitchbond polyester is a 3 ounce per square yard stitched polyester fabric. This polyester fabric readily conforms to imbedded gravel and standing seam metal roof decks and works well with solvent asphalt roof coatings and water asphalt emulsion roof coatings. High degrees of strength and elongation accommodate normal expansion and contraction of roofs.

Uses

- Cold process roofing systems, roof repair and waterproofing.

Advantages

- Excellent tensile strength.
- Excellent elongation.
- Quickly and easily saturated with a wide variety of coatings.
- Conforms easily to irregular substrates.
- Lightweight.

Restrictions

- Do not use with hot application. Do not stretch prior to or during application.

PACKAGING INFORMATION

<u>Product Number</u>	<u>Size</u>	<u>Quantity</u>	<u>Weight</u>
94440	40" x 324'	1 Roll	25 lbs