

# REPELZ WET LOOK CONCRETE SEALER

Product # **A37005 – Clear**  
**A37105 – Honey Brown**



**Description:** A water-based polymer blended concrete sealer specifically designed to give a truly natural look to the surface without appearing overly glossy or slippery. This sealer cures to a clear, beautiful matte finish that will not yellow, chalk, or darken over time. Its durability and outstanding adhesion protect against weathering, traffic, de-icing salts, and chemical staining.

**Uses:** All aged concrete finished surfaces including driveways, sidewalks, patios, and pool decks. Perfect for broom finish, acid-stained exposed aggregate, stamped, precast pavers, decorative overlays, and terrazzo surfaces.

**Coverage Rate:** 200 - 300 ft<sup>2</sup>/gallon

## Advantages:

- **LONG LASTING PROTECTION**  
10 years of UV resistance. Protects against weathering, traffic, de-icing salts, and chemical staining.
- **NATURAL LOOK**  
Does not whiten in damp conditions. Does not yellow with age and minimal darkening
- **NO MIXING REQUIRED**  
Product is ready to use from container and does not need mixed or thinned.
- **EXCELLENT TRACTION**  
Does not need matting agents or anti-slip additives.

**Shelf Life:** 2 years in unopened container stored between 40°F - 90°F

**Preparation:** Make sure surface is free of any debris, stains, and standing/ponding water prior to application. For best results, avoid applying in foggy, rainy, or excessively hot weather. Do not apply if precipitation is forecasted within 12 hours.

**Mixing:** Storm Shield Waterbased Concrete Sealer is ready to use from container and no mixing is required. Do not thin with water.

**Application:** Storm Shield Waterbased Concrete Sealer is designed for use in a pump sprayer, however, product can also be applied with a brush or roller. Maintain a wet edge while spraying to ensure one even coat over the entire surface. Avoid any puddling of material.

**NOTE:** Overapplication of material may cause bubbling, whitening, peeling, loss of adhesion, and/or flaking.

## PROPERTIES

Dry to Touch	2-4 Hours
Foot Traffic	6-8 Hours
Vehicle Traffic	16-24 Hours
Ready for 2 <sup>nd</sup> Coat	Minimum 2 Hours
VOC's	0 g/l
Meets ASTM C-309 for moisture loss (<0.40 kg/m <sup>2</sup> )	

**Cleaning and Removal:** Clean tools and equipment with ALCM Power Clean. To remove material from concrete, use a heavier amount of ALCM Power Clean, wait 5 minutes, then scrub area with a stout brush or broom. Sandblasting or other mechanical means may also be used to remove product from the surface.

Contact FBC Chemical Corporation sales and technical service for any questions regarding the application of this product.

**Precautions:** Review product SDS prior to use. Do not apply if threat of precipitation within 12 hours of application. Do not apply over puddled or standing water. Do not apply in excessive cold (<40°F) or high heat (>90°F) or bubbling and other issues can occur. Do not apply the product thicker than the recommended. This can cause failures such as bubbling, whitening, peeling, loss of adhesion and/or flaking. Do not thin. Applying two coats of material may need to have anti-slip additives incorporated

Visit [alcm.com](http://alcm.com) for info on our entire product line.