

# REPELZ WOOD SEALER

Product # **A38005, A38055 – Clear**  
**A38105, A38155 – Honey Brown**



**DESCRIPTION:** A waterbased polymer blended wood sealer specifically designed to give a truly natural look to the surface without appearing overly glossy or slippery. This sealer cures to a clear, beautiful matte finish that will not yellow, chalk, or darken over time. Its durability and outstanding adhesion protects against weathering, traffic, de-icing salts, and chemical staining.

**Uses:** Use to seal a wide variety of interior and exterior wood surfaces. Can be used to seal aged concrete surfaces as well.

- Outdoor: Decks, fencing, wooden furniture, raised garden beds, decorative landscapes, boardwalks, and more.
- Indoor: Window frames, doors, ceiling beams, railings, tables, chairs, cabinets, and more.

**Coverage Rate:** 200-300 ft<sup>2</sup>/gallon

*\*Two coats recommended for freshly poured concrete surface and if additional sheen is desired.*

## **Advantages:**

- **LONG LASTING PROTECTION**  
Helps to cure and seal freshly poured concrete surfaces and serves as a protective sealer for older, cured concrete surfaces.
- **NATURAL LOOK**  
Will not whiten in damp conditions. Will not yellow or discolor over time.
- **READY TO USE**  
Protects concrete from weathering, chemical staining, de-icing salts, traffic, and oil/gasoline.
- **ZERO VOC'S AND SOLVENT FREE**  
Safer, less odor, and easier clean up over solvent based wood sealers.

**Shelf Life:** 2 years in unopened container stored between 40°F - 90°F

**Preparation:** Make sure wood surfaces are free of any debris, stains, and standing/ponding water prior to application. Remove as much of old stain as possible. Sand away any opaque paint. For best results, avoid applying in foggy, rainy, or excessively hot weather. Do not apply if precipitation is forecasted within 12 hours.

**Mixing:** *Repelz Wood Sealer* is ready to use from container and no mixing is required. Do not thin with solvents.

**Application:** *Repelz Wood Sealer* is designed for use in a pump sprayer, however, product can also be applied with a brush or roller.

- IF ROLLING: Apply and back roll to avoid excessive coverage. Avoid excess puddling.
- IF SPRAYING: Maintain a wet edge to ensure one even coat over the entire surface. Avoid excess puddling.

**NOTE:** Overapplication of material may cause bubbling, whitening, peeling, loss of adhesion, and/or flaking.

## PROPERTIES

Dry to Touch	2-4 Hours
Foot Traffic	6-8 Hours
Ready for 2 <sup>nd</sup> Coat	Minimum 2 Hours
VOC's	0 to trace g/l
Meets ASTM C-309 for moisture loss (<0.40 kg/m <sup>2</sup> )	

**Cleaning and Removal:** Clean tools and equipment with ALCM Power Clean. To remove material from concrete, use a heavier amount of ALCM Power Clean, wait 5 minutes, then scrub area with a stout brush or broom. Sandblasting or other mechanical means may also be used to remove product from the surface.

Contact FBC Chemical Corporation sales and technical service for any questions regarding the application of this product.

**Precautions:** Keep out of reach of children. Review product SDS prior to use. Do not apply if threat of precipitation within 12 hours of application. Do not apply over puddled or standing water. Do not apply in excessive cold (<40°F) or high heat (>90°F) or bubbling and other issues can occur. Do not apply the product thicker than the recommended. This can cause failures such as bubbling, whitening, peeling, loss of adhesion and/or flaking. Do not thin. Applying two coats of material may need to have anti-slip additives incorporated.

**Visit [alcm.com](http://alcm.com) for info on  
our entire product line.**