



ASPHALTIC ROOF RESATURANT/COATING

(PRODUCT # 81350)

DESCRIPTION: #81350 contains a high quality asphalt blended with selected grades of penetrating oils plus fibers to produce a highly durable homogeneous product.

USES: Excellent for gravel roofs, to penetrate and provide protection for extended roof life. Coal tar gravel roofs must be at least five years old.

APPLICATION:

1. Remove all loose gravel.
2. Sweep roof thoroughly, removing all dirt, dust and debris. If necessary, flush with water hose to remove all silt.
3. Make all required repairs to cracks and breaks.
4. DO NOT thin coating. Spray or brush Asphaltic Roof Resaturant/Coating on roof at a rate of 3 to 5 gallons per 100 square feet. (Amount varies with condition of roof)
5. Badly worn roofs, apply heavy initial coating over entire roof, embedding 36" Membrane into coating. Use brush to work out all wrinkles. Overlap sides of Membrane 4" and ends 8". Apply top coating over entire area.

SPECIFICATIONS: Meets Federal Specification Spec SS-A-694D

Solids	62%
Volatile	38%
Asphalt	57%
Consistency	Suitable for spraying or brushing at normal temperatures.
Drying Time	To touch – 48 hours
Color	Black
Flash Point	105 Degrees F.
Viscosity (ASTM D217)	80 Degrees F. 325-375

PACKAGING: 55-gallon drum (500 lbs.)
5-gallon pail (45 lbs.)