



**#1 SPECIAL HEAVY MASTIC**  
(Product #8050)

**USE:** As a protective coating for metal roofs, smooth surfaced asphalt roofs and coal tar gravel roofs over five (5) years old. For coating built-up, composition, felt, fabric and masonry roofs and parapet walls. Can be sprayed on side wall up to ¼" build (wet) before sagging.

**DESCRIPTION:** A fibrated petroleum asphaltic compound made from highly ductile asphalt, blended with specially selected solvents, drying oils and mineral fillers including fiberglass strands for reinforcement. Upon drying, it produces a tough elastic film.

**SPECIFICATION:** Meets Federal Spec. SS-R-451  
Solids: Approximatley 61%  
Consistency: Suitable for spraying or brushing at normal temperatures.  
Drying Time: To touch – 24 hours  
Color: Black

**APPLICATION:** Applied by a 4-knot roofer's brush, a soft fiber push broom, or heavy duty air motor roof spraying equipment. Roof must be dry. Surfaces must be swept clean and rust removed from metal. If necessary, repair blisters and loose seams before coating.

**COVERAGE:** 3 Gallons per 100 square feet. (Coverage is approximate and may vary based on age, porosity, and type of roof surface.)

**PACKAGES:** 55 Gallon Open Head Drums and 5 Gallon Pails

**SHIPPING WEIGHTS:** Drums – 515 lbs. Pails – 47 lbs.

This coating has been laboratory tested and field-tested and in both cases the results have been excellent. It has been widely used by industrial accounts for over 19 years and has been well accepted and incorporated in maintenance planning.

## #1 SPECIAL HEAVY MASTIC

### SPECIFICATIONS:

Meets ASTM Specifications ASTM 4479 (Asbestos Free)

|   |                                  |
|---|----------------------------------|
| Flash Point   | 105 Degrees F                    |
| Weight, lbs./gal.   | 9.1                              |
| Consistency   | Spray, light trowel,<br>or brush |
| Non-Volatile  | 66%                              |
| Film Appearance   | Black Mastic Type                |
| Avg. coverage of coating for 1/16" dry film                           | 16 sq. ft./gallon                |
| Avg. drying time of 1/16" wet film,<br>50% R. Humidity, 70 Degrees F. | Touch: 3 hours<br>Set: 24 hours  |
| Water vapor permeability at 90 Degrees F,<br>Perms, 1/8" dry film     | Less than 0.02                   |

CAUTIONS: COMBUSTIBLE. Contains petroleum distillates. Keep away from heat, sparks, and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid breathing of vapors. Do not take internally.

KEEP OUT OF REACH OF CHILDREN.